



Applied Pulsed Power, Inc.™

2025 Dryden Road
P.O. Box 348
Freeville, NY 13068

Phone: 607-844-3426
Fax: 607-844-3428
www.appliedpulsedpower.com

Model S32 5kV Solid State Trigger Generator

The S32 5KV Trigger Generator has a 5KV power supply and high current switch for charging and discharging an external capacitive load. The switching is controlled by a model S25 high voltage solid state switch. Optoelectronic controls and 12VDC power requirements allow isolated operation.



This Trigger Generator features:

- 2 ST style 62.5/125µm Control Channels
- 3 ST style 62.5/125µm Status Channels
- Low Inductance
- Can be used in place of krytron triggered systems
- Isolated operation

Operational Characteristics

Input Voltage	12	VDC
Maximum 12VDC power supply current	1	A
Quiescent 12VDC power supply current	20	mA
5KV charging current	1.2	mA
Charging Resistance	2.2	MΩ
Peak Current	14	KA
Peak di/dt	30	kA/µSec
Typical Delay Time	100	nSec
Typical Delay Jitter	2	nSec
Dimensions	7 x 4.25 x 2.25	Inch

The S32 can be configured for operation at higher voltages with smaller charging currents. Also, the S32 can be configured with high current contacts to fit custom connection needs. Please contact Howard Sanders hds@appliedpulsedpower.com for more details.